Marco D. Boscardin, Ph.D., P.E., D.GE, F. ASCE

Consulting Engineer 53 Rolling Ridge Road Amherst, MA 01002-1420 June 2013 413-549-3804 Office 413-237-4852 Mobile

EDUCATION

Ph.D., Geotechnical Engineering, University of Illinois at Urbana - 1975-1980 M.S., Geotechnical Engineering, University of Illinois at Urbana - 1974-1975 B.S., Civil Engineering, Massachusetts Institute of Technology - 1969-1973

PROFESSIONAL REGISTRATION

Registered Professional Engineer, State of Illinois (062-039449) – 1981 to date Registered Professional Engineer, Commonwealth of Massachusetts (34186-C) – 1988 to date Licensed Site Professional, Commonwealth of Massachusetts (5573) - 1994 to not current Also a Professional Engineer in New York, New Jersey, Connecticut, Pennsylvania, New Hampshire and Vermont

PROFESSIONAL SOCIETIES

Academy of GeoProfessionals - Diplomate, Geotechnical Engineer

American Society of Civil Engineers - Fellow

American Concrete Institute

American Society for Testing and Materials

ASFE – The Geoprofessional Business Association

Association of Engineering Geologists - Affiliate Member

Deep Foundations Institute

Geo-Institute

International Society of Soil Mechanics and Foundation Engineering

International Tunneling and Underground Space Association

LSP Association

North American Trenchless Technology Society

The International Association of Foundation Drilling - Technical Affiliate

The Underground Construction Association of SME

GENERAL BACKGROUND

Dr. Boscardin has over 30 years of experience which includes geotechnical engineering with emphasis on underground construction, excavation support, and shallow and deep foundations. Dr. Boscardin's background includes soil and rock tunneling, trenchless construction, excavation support, foundations, building and utility response to nearby construction, soil and rock laboratory testing, slope stability, dams, blasting, dewatering, grouting, contaminated site assessment and remediation, geotechnical instrumentation, and forensic and claims-related services.

REPRESENTATIVE EXPERIENCE

Forensic and Claims Related Experience

- Surcharge Loading and Settlement, N. Bergen, NJ Provided litigation support services related to a claim regarding preloading an area augmented with wick drains to expedite drainage and consolidation of silt and clay deposit.
- TVA Ash Pond Dike Evaluation, Kingston, TN Retained by the Insurer to perform a preliminary forensic review of records leading up to and following the December 2008 failure of fly ash pond containment dikes at the Kingston Fossil Plant.
- **Elementary School, Hatfield, MA** Provided engineering services related to a claim regarding frost heaving of sidewalks that went to Arbitration.

M. D. Boscardin

Biodata

Page 2

June 2013

• **Telecommunications Lines, Newark and Edison, NJ** – Provided engineering services related to investigation of two claims associated with horizontal directional drilling and conduit installation and collapse during grouting.

- North Shore Connector, Pittsburgh, PA Provided engineering services and presented to a Disputes Review
 Board regarding a tunneling differing site condition related to excavation and behavior characteristics of claystone
 and amount of fines generated during mining.
- **Planet Hollywood, Boston, MA -** Provided engineering services and litigation support related a claim regarding building damage, excavation support, and sheet pile driving vibrations and related settlement.
- Antelope Island Borrow, Salt Lake City, UT Exploration and evaluation of a large, 10 million cubic yards borrow source on Antelope Island. Borrow used to construct fills associated with I-90 construction. Included litigation support services.
- **Farmington Bridge, Farmington, NH -** Provided engineering services and litigation support for an excavation support, bridge sheet pile cofferdam driving construction claim.
- Long Branch, NJ Evaluation and claims support related to sheet pile cofferdam flooding and by-pass pumping.
 The temporary cofferdam was constructed to permit construction of bridge piers and abutments for a bridge reconstruction across a narrow lake. Served as expert witness for an arbitration hearing.
- Colonie, NY Provided litigation support services regarding wetlands construction impacts on the stability of a soil slope in overconsolidated clays and associated damage and repairs to existing pipelines and structures.
- **Boston, MA** Provided litigation support services related to bentonite slurry composition and performance, and its role in slurry wall construction.
- Boston, MA Provided DRB support services related to tunnel leakage performance and slurry wall construction methods and details.
- Boston, MA Provided claims support services related to ground freezing impacts on performance of underground structures.
- **Perry's Victory National Park, OH** Evaluated alternative design submittals related to claim for a seawall foundation in rock. Included concrete key and caisson alternatives to resist horizontal loadings.
- Route 101, Candia-Raymond, NH Provided engineering services and litigation support for a highway rock
 excavation construction claim.
- Napa, California. Provided litigation support services regarding a sheet pile wall microtunneling cofferdam design and performance.
- Soil Nail Wall South Hadley, MA Performed a forensic evaluation for a claim regarding the performance of a soil nail wall used as excavation support during construction of a college dormitory. The soil nail wall was constructed in glacial lake deposits and subjected to heavy rain events that affected its performance.
- Structural Evaluation of Damage to Existing Buildings Former MGP Site, Suffern, NY Technical Consultant for evaluation of damage to existing structures related to settlement of foundations. Existing buildings were constructed above former MGP site facility structures. Project included evaluation of structural condition of building due to damage to date and recommendations for additional supports/repairs to existing walls.
- Perimeter Road, Manassas, VA Investigation of pavement condition and development of recommendations for reconstruction in areas of pavement failure at IBM Building No. 250.

M. D. Boscardin
Biodata
Page 3
June 2013

Excavation and Building Response, Instrumentation Experience

• UMass Boston, Integrated Sciences Complex, Boston, MA – Design engineer of record for contractor installing controlled modulus column (CMC) elements approximately 25 to 30 feet deep to support utilities and surface landforms for the complex. The site is reclaimed land and includes granular fill over miscellaneous land fill, cohesive fill over soft organic soils over deep marine sands and clays. Bearing strata for buildings is on the order of 100+ feet below the existing ground surface. The building is supported by deep foundation elements designed by others. Tasks included reviewing/checking/approving CMC design computations and drawings; assisting in planning, performing and evaluating a CMC load test; performing periodic site visits to observe CMC and load transmitting platform (LTP) construction; meeting with site construction personnel, project designs and construction manager personnel to address changes and issues that arose during construction.

- Pearl Harbor Memorial Bridge, New Haven, CT Technical reviewer and consultant for cofferdams and base mats to support vibratory caisson construction equipment for large bridge foundation element installations in organic silts over sand. Considerations included dynamic and static deformation moduli of the soft/weak silts, potential settlements and bearing pressures. Project also included foundation considerations for crane support mats on fills over the silts for existing bridge demolition.
- Upper Saucon, PA Conceptual phase consultation and evaluation regarding potential for mine subsidence and related impacts on the design and performance of a large, secure data facility composed of two, 400-ft by 600-ft main buildings and a number of smaller support structures sited over the footprint of an abandoned mine. Risk issues considered included potential for and likely magnitude of subsidence associated with abandoned zinc mine complex 700 to 1200 feet below the ground surface and the deformation and performance issues likely for the various structures to be located above and near the mine. The host rock for the mine is limestone and karst features were also a consideration in the site development and conceptual foundation design.
- Lopatcong, NJ Consultation and review regarding foundation design for a large secure facility in a area with karst
 (solution limestone) ground conditions. Foundations systems considered included 4 to 6 ft diameter drilled shaft and
 large spread footings as well as a mixed system. Key issues included detection of solution activity zones at specific
 foundation element locations, verification methods to employ during construction, bearing capacity and settlement.
- Albany Hospital, Albany, NY Consultation related to evaluating ground movements and related risks associated with braced excavations, 20 to 30 feet deep, in a deep deposit of soft to very soft varved clay including potential impacts to adjacent buildings and utilities. Considerations included global stability of the excavations, large surcharge loadings due to nearby buildings, applicable support of excavation (SOE) types and stiffenesses and ground improvement options.
- Capitol Visitors Center, Washington, D.C.-Technical review and oversight of slurry wall and tieback excavation support system temporary works design for the Contractor of a 55-foot deep, approximately 300 feet by 500 feet excavation for an underground visitors center for the United States Capitol Building in Washington, DC. The excavation is to within 2 feet of the Capitol Building which is supported on shallow foundations. Tasks included evaluation of impacts of construction on the building, design of slurry wall and tiebacks for the temporary construction loads.
- Caton Place, Brooklyn, NY Pre-bid evaluation of soldier pile and lagging and secant pile excavation support system options, as well as, raker, cross-lot and tieback bracing support options and adjacent building protection/underpinning.
- South Ferry Terminal, New York, NY Pre-bid evaluation of a composite jet grout, micropile excavation support system option, to limit ground movements and ground water inflow while protecting overlying existing subway tunnel relative to excavation induce ground movements.
- Barclay Street, New York, NY Pre-bid evaluation of a tied back secant pile wall excavation support system alternative, and related adjacent building protection.

M. D. Boscardin

Page 4

Biodata

June 2013

 Citizen's Gas Works/Carroll Gardens, Brooklyn, NY – Preliminary design recommendations for excavation support system to permit excavation during MGP contamination remediation. Key issues included limiting deflections and damage to roads, utilities and a nearby building and dewatering concerns. SOE alternatives considered included driven steel sheet piling and solder pile and lagging systems.

- Building Compensation Grouting, Spadina Subway Extension, Toronto, Canada Technical review of compensation grouting design and report and risk evaluation for protection of a 3-story university building where twin, 20-ft-diameter subway tunnels are to be constructed about 28 feet directly below the building foundations and a 65-foot-deep braced excavation is to be constructed 15 feet from the building. The ground conditions consist of fill over medium dense to very dense glacial till and glaciolacustrine sands, silts and clays.
- MBTA Light Rail Accessibility Program at Copley Station, Boston, MA Provided geotechnical and building response consulting services for construction of a new elevator access shaft to an underground subway line in close proximity to a historic church. We were brought in mid-project to develop building, ground movement and excavation support movement and deformation criteria after construction jet grouting activities were observed to be impacting the church in order to safely expedite completion of construction. Tasks included reviewing past and current construction activities and building response data, setting criteria for ground and building response to permit completion of the work while protecting and managing risk to the historic fabric of the structure, inspecting the structures foundations and façade via test pits and boom lifts, reviewing results of pile load tests on existing timber piles supporting the church, reviewing SOE and dewatering construction submittals to complete the work, reviewing and developing recommendations for building, ground and excavation instrumentation which included automated data acquisition, and reviewing instrumentation data. Instrumentation included automated total station surveying of the façade of the church, in place inclinometers between the excavation and church, convergence gages in and crack gages on the church, seismographs, piezometers and observations wells accessible remotely via a web-based system. Dewatering included recharge wells to maintain water levels and limit related impacts on the church on other nearby structures and utilities. Geotechnical related construction activities included jet grouting, secant pile installation for SOE and shaft bottom stability, and demolition of an existing MBTA access stairway.
- Castalia Pump Station, Castalia, OH Analyzed base heave mechanisms of pump station excavation that had
 already experience base heave and prepared remedial construction and excavation bracing design recommendations
 to permit completion of excavation and construction.
- Shands Hospital, Gainesville, FL Design of a soldier pile and lagging excavation support system in the Miami limestone for an addition for the University of Florida Shands Hospital.
- 10 St. James Avenue Development, Boston, MA Provided earth support system for installation of slurry walls used as permanent walls for a 4-story underground parking garage below a 21-story building. Designed walls for temporary loads during construction, and bracing to facilitate up-up construction techniques requiring coordination between bracing installation and removal and construction of building framing. The excavation was adjacent to two existing buildings and is founded below the existing foundations for both buildings. Design included evaluation of bracing system movements, groundwater control and impacts on adjacent structures as well as value engineering redesign of wall layout to improve schedule and reduce dewatering.
- Harvard Medical School Research Building, Boston, MA -Technical consultant for design of slurry wall earth
 support system in deep marine clay and sand deposits. Slurry wall support system to be used as permanent walls for
 multi-story building with two stories of underground parking. The excavation support system was designed for an
 excavation of up to 50 feet below existing ground surface adjacent to several buildings. Design included evaluation
 of bracing system movements and impacts on adjacent structures as well as value engineering redesign of wall
 layout to improve schedule and reduce dewatering.
- Former Manufactured Gas Plant, Beardstown, IL Provided preliminary design of a braced steel, sheet pile wall to support an excavation between an existing building and the toe of an existing levee. Developed recommendations and specifications for final design including special equipment to minimize settlement of building footings founded in loose soils.

M. D. Boscardin

Page 5

Biodata

June 2013

• **Jones Island Shaft, Milwaukee, WI** - Evaluation of settlements due to dewatering of soft estuarine clays during construction for a 12-foot-diameter, 200-foot-deep shaft associated with a deep storm water detention system.

• Central Artery/Tunnel Project, Immersed Tube Tunnel, Contract C05A1, Boston, Massachusetts Project manager in charge of installing instrumentation and monitoring performance of tangent pile walls and slurry walls for East Boston (a secant pile wall) and South Boston area (a 250-ft-diameter, 85-ft-deep circular diaphragm wall) cofferdams during construction of the tunnel. Instrumentation included slope inclinometers, piezometers, surface settlement points, building settlement points, and deformation monitoring points. Purpose of instrumentation was to provide data on the performance of the slurry and tangent pile walls relative to excavation support and ground water control as well as performance of excavation slopes during construction of the ITT.

Tunneling Related Experience

- Clean Water Project, MDC Hartford, CT Provided geotechnical, underground construction and GDR/GBR reviews and claims support related to soil and rock tunnels and microtunnels as well as related structures for the MDC's CWP. Projects included curved microtunneling in varved clay soils, excavations for treatment plant facilities and 20+ foot diameter, 3 mile long deep rock storage tunnel.
- Transbay Transit Center Project, San Francisco, CA Performed a Peer Review and Value Engineering services at the preliminary design level for approximately 1.3 miles of cut-and-cover and mined railroad and transit tunnels and related stations. Issues addressed included construction methods, risk and mitigation of construction impacts on adjacent structures and utilities, tunnel and station waterproofing, soil-structure interaction, construction dewatering, types of excavation support, and project risks.
- SR99 Bored Tunnel Alternative, Seattle, WA Served as reviewer of planned tunnel settlement and building and utility response mitigation measure reports for the design-build team that was selected to construct an approximately 57-foot-diameter, 1.7 mile long highway tunnel in soil up to 250 feet deep under downtown Seattle. Also, serving on the expert review panel for the design-build team during final design and construction. Key aspects include evaluating risk, controlling face pressures to balance high water pressures and control tunnel face ground loss, and protection of structures affected by the highway tunnel construction including modern and historic buildings, a viaduct structure and the BNSF Railroad tunnel. Tunnel construction and building protection measures considered included secant piles, compensation grouting, jet grouting, micropiles, underpinning, and building strengthening.
- Eglinton Subway Line, Toronto, Canada Prepared and revised jet grouting specifications and test program for tunnel shaft entrance and exit eye ground stabilization for 7 shaft locations on the Eglinton-Scarborough Crosstown Twin Tunnels project. Key issues included strength, stability, continuity, and permeability of the head walls.
- North Shore Connector LRT Project, Pittsburgh, PA Developed building protection and underpinning design and construction recommendations for approximately 6,700 feet of mined twin tube light rail transit soil and rock tunnels with stations passing under the Allegheny River and in downtown Pittsburgh. Potentially affected structures include historic buildings and ramps, aerial highway structures and utility lines adjacent to TBM mined tunnels, and slurry wall, deep soil mix wall, sheet pile wall and soldier pile wall excavation support systems. Project design included jet grout, compaction grouting, permeation grouting ground improvement to limit ground movements and related building movements during tunneling and open cut excavation, and preparation of a geotechnical baseline report (GBR). Provided construction phase services related to instrumentation, jet grouting, and tunneling which included responding to RFIs reviewing submittals, mix designs and field data, meetings with the owner and contractors, participating in test sections, reviewing DSC submissions and assisting in disputes review board (DRB) presentation preparation.

M. D. Boscardin

Page 6

Biodata

June 2013

MBTA Silver Line Phase III, Boston, MA - Developing geotechnical design and construction, and risk mitigation
recommendations, building and transit station protection/underpinning design and construction recommendations,
and excavated materials management specifications for an approximately 4,000-foot-long, twin tube, mined and
open cut underground bus rapid transit tunnel through marine deposits, glacial till and rock in a dense urban setting.
Construction methods considered include TBM mining, NATM mining, open cut excavation with slurry walls, jet
grouting ground improvement, secant pile walls, and underpinning.

- Miramar Water Treatment Plant Upgrade and Expansion, San Diego, CA Participated in developing design recommendations and later reviewed contractor tunnel construction, support, instrumentation and grouting submittals for the design team/owner for open cuts and tunnels constructed under existing sedimentation basins. Twelve-foot-diameter horseshoe-shaped tunnels to house 120-inch-diameter pipes were constructed in the Stadium Conglomerate directly beneath two sedimentation basins. The tunnels were mined using roadheaders and hand mining methods with spiling and shotcrete with steel ribs support. The key issue was to perform the construction with little impact to the serviceability of the sedimentation basins so that they could continue function following the construction.
- West Roxbury Sewer Tunnel Rehabilitation, West Roxbury, MA Performed geotechnical and contaminated
 materials evaluation and management for conceptual design of alternatives for repair, rehabilitation and replacement
 of 12,500 ft of 7-ft-diameter, rock tunnel and 1000 ft of soil tunnel. Evaluated new rock tunnel construction, slip
 lining of existing tunnel and spray on lining. Performed geotechnical and contaminated soils management services
 for final design and construction of the slip lining of the 1000-ft soil tunnel.
- MBTA South Boston Piers Transitway, Boston, MA Developed geotechnical design and construction recommendations and provided construction support services for a 1,600-foot-long underground bus tunnel located in a dense urban environment. Tunnel sections include cut-and-cover tunnels, an immersed tube tunnel, a NATM mined tunnel using ground freezing to control groundwater and support two existing 7-story historic buildings during tunneling directly under the buildings, and installation of slurry walls for future adjacent construction. The tunnel structure included a sealed membrane liner. Important aspects of the project include design and construction monitoring of foundation and excavation systems and underpinning to minimize impacts on adjacent structures, utilities, and future construction, design of instrumentation systems to provide data to monitor progress and impacts of the construction and provide a basis for adjusting the foundations of the buildings to control damage, pile foundations for reconstructed wharfs, and evaluation and monitoring of existing historic seawalls adjacent to and above open cut and tunnel construction, and design of a permanent groundwater pressure relief system for an existing station affected by the new construction. Design included soil mix subgrade struts to stabilize an open cut with a soft bottom. The soil mix was replaced with jet grout based on acceptance of the Contractor's value engineering proposal. Services during construction included submittal and instrumentation data review and evaluation, planning periodic adjustments of the buildings' underpinning, monitoring jet grouting, compensation grouting, mini pile installation and other geotechnical construction at the site.
- Four Mile Fork Drainage Basin Tunnel, WV Developed design and specification recommendations for excavation and support of an unreinforced concrete-lined dam diversion tunnel in sandstone and shale.
- **Burlington Tunnel, Burlington, VT** Provided rehabilitation/report design and construction recommendations for a 340-foot-long brick masonry-lined railroad tunnel originally built in 1860/1861. The tunnel was taken out of service for repairs to the deteriorated surface of the brick lining and to allow lowering of the invert of the tunnel to improve clearances. The tunnel lining is an elliptical-shape horseshoe configuration supported limestone footing blocks. Based on historic reports, the 1860's tunneling encountered what appear to be running sand conditions that made the stabilization and control of the ground during the original mined construction difficult. Rehabilitation construction design addressed, removal of invert of tunnel and impacts on tunnel lining stability and movements before and during construction. Rehabilitation construction included removal, lowering, and re-installing the tunnel invert, application of shotcrete to deteriorated sections of tunnel lining, and grouting of lining to repair existing cracks in the masonry.
- Central Artery/Tunnel Project, Tunnel Jacking, Contract C09A4, Boston, MA Providing geotechnical and temporary works, and tunnel jacking design services to contractor for installation, via tunnel jacking, of four tunnels

M. D. Boscardin
Biodata
Page 7
June 2013

under multiple commuter and Amtrak railroad tracks. Tunnels range in size up to 80 feet wide by 40 feet high by 350 feet long. Issues being investigated include controlling ground movements affecting the railroad facilities during and after construction excavation, ground stabilization by ground freezing, jet grout base slab support, slurry wall headwall design and developing jacking reaction.

- Staple Bend Tunnel, PA Technical consultant for design of rehabilitation measures for a 900-ft-long, horseshoe-shaped soil and rock tunnel 19 ft wide by 20 ft high. This is a historic tunnel, circa 1833, reportedly the first RR tunnel and the third tunnel overall constructed in the US. Ends are in soil with masonry and concrete lining (150 ft) and the central 600 ft is unlined rock tunnel. Tunnel is being rehabilitated for public access while retaining historic elements, e.g. portal facades, masonry lining and interior rock exposures. Investigation program included detailed mapping of tunnel condition, borings in portal areas and limited test pitting of the tunnel floor. Designed repairs include rebuilding facade retaining structures, installing spot rock bolts, repointing masonry lining and installing shoring post in overhang areas.
- The New-Gate Prison and Copper Mine, CT Inspected the condition of the mine, evaluated the safety of the mine for public access, and developed recommendations regarding support maintenance, support replacement, loose rock removal, and new support installation needs for continued safe public access. The mine is a historic site that is open to the public, including underground tours of the mine. The copper mine was reportedly first put into service circa 1705. The mine was later used as a prison from 1773 to 1827. Also performed follow up inspection and recommendations 7 years later.
- Greenup Lock Extension, Culvert Bypass Alternatives Analysis, KY Technical lead for the alternatives analysis that investigated 15 different options for installing a culvert around the existing 600-ft lock to provide filling capacity for the 600-ft lock extension on the Ohio River. Open cut, braced sheet piles, braced slurry walls, and various tunneling options were considered. Each alternative was examined with respect to cost, constructability, and risks associated with construction and expected costs. The most economic and viable options resulting from the analysis were the combination of an open cut with a braced slurry wall or braced sheet pile wall.
- Central Artery, DO14C and D017A Design Sections, Boston, MA Task manager for subsurface investigation, laboratory testing, data analyses, and data and engineering report preparation. Subsurface investigations included standard penetration test borings, thin-walled tube sampling, rock coring, cross-hole seismic tests, water level and pressure monitoring, borehole permeability testing (packer, constant head, and variable head methods) and site hydrogeology. Also directed *in situ* testing including pressuremeter, dilatometer, and field vane tests for the Central Area. Laboratory testing included sample radiography, standard index tests, triaxial strength testing (compression, extension, and K_o), direct simple shear tests, consolidation tests, and dynamic triaxial tests. Data analyses were performed to develop subsurface profiles, to estimate soil properties, and to provide soil and rock parameters and geotechnical design and construction recommendations for use by the Section Design Consultants. Geotechnical design issues included soil and rock excavation, slurry walls for excavation support, pipe jacking and tunneling for utility line relocations, water control during construction, seismic loads, and effects of construction on adjacent structures, utilities, and tunnels.
- Stillwater Tunnel, Utah Monitored rock tunnel instrumentation. Instrumentation included vibrating wire strain gages on steel ribs, inclinometers (oriented horizontally for tunnel crown observations), a curvometer (for change in curvature of steel ribs), and a deflectometer (tunnel springline movements) for a water transmission tunnel.
- Metro System, Washington, D.C. Collected tunnel-induced ground deformation data and building performance data during construction of stations and tunnels for the G-1 and F-2 lines of the Metro construction and used the data to develop building response estimation and damage criteria. Later worked on several station and tunnel construction projects (E1-d, Shaw Station, Navy Yard Station) as consultant to the contractor developing building impact and risk of damage estimates due to construction of stations by open cut methods, and 21-ft –diameter tunnels using EPB (with compressed air back up) methods, developing and implementing building monitoring systems, mining and lining back grouting sequencing, dewatering, and compaction grouting ground improvement and mitigation plans.

M. D. Boscardin

Page 8

Biodata

June 2013

• Chambers Reservoir Project, Douglas County, CO - Preliminary design phase geotechnical investigation consultation for an intake shaft (approximately 20 ft by 29 ft) and inlet pipelines (approximately 4 feet diameter and 100 and 250 feet long). The upper portion of the dam embankment is consists of sand and clay soils over claystone and conglomerate bedrock. The intake shaft penetrates about 40 feet into the claystone and the lower inlet pipeline is to be installed using trenchless construction methods (pipe jacking, microtunneling or horizontal auger boring). Key issues include swell potential of the clays and claystone, strength of the claystone and stickiness and clogging protential of the clay and claystone relative to shaft construction and trenchless construction methods selected.

- San Vicente Bypass Pipeline Project, San Diego County, CA Tunnel design consultant for proposed new 4-to-5-ft-diamter by pass water pipeline. Proposed bypass alignments range from approximately 1500 ft long to 2700 ft long with about 900 ft in a recently placed engineering fill and 600 to 1800 ft in rock (conglomerate and granite). Construction methods considered include microtunneling/pipe jacking and a mined, horseshoe-shaped tunnel constructed using drill-and-blast and/or road header excavation techniques. Key issues are risks to and protection of new marina structures in the fill portion of the project during construction and widely varying ground, strength and abrasivity conditions in the rock affecting tunnel constructability decisions.
- MDC Clean Water Program, Phase I, Hartford, CT Project manager and technical lead for the team providing project-wide geotechnical services to The Metropolitan District Commission and their program management unit. The overall program includes approximately 60 miles of new sanitary sewers; 20 miles of tunnels and conduits; and related headworks and pumping stations with an estimated Phase I construction cost of \$800,000,000. Tasks included developing program-wide: an updateable program database of available geotechnical information for use during design of various project segments; a soils management plan and excavate analysis; a geotechnical QA.QC plan and procedures; and a contaminated soils management plan. Additional Task Order Services included: preliminary design subsurface investigations of geotechnical and contaminated ground conditions and related recommendations; value engineering and constructability reviews of the geotechnical and contaminated materials aspects (including instrumentation, building protection, and geotechnical baseline reports) of final designs and risks for trenched, trenchless (e.g. pipe jacking and microtunneling) and deep storage tunnel construction prepared by others; and construction phase support including contaminated material management and disposal, differing site conditions evaluations, and geotechnical instrumentation evaluations.
- Miscellaneous Gas Pipeline Projects NY and MA Performed feasibility and prepared layout design recommendations for 6 to 10-inch-diameter steel and HDPE gas pipeline crossings of highways, wetlands, other environmentally sensitive areas using HDD, microtunneling, pipe jacking and horizontal auger boring methods. Crossings ranged from 80 to 1000 feet in clay, sand and glacial till soil conditions.

M. D. Boscardin

Page 9

Biodata

June 2013

• Homestead Avenue Interceptor Extension – MDC - CWP, Hartford, CT - Performed design phase value engineering reviews, constructability reviews, and geotechnical baseline report (GBR) reviews. Also provided construction phase services including review and recommendations related to automated instrumentation, pilot tube microtunneling, and the first curved microtunnel installation in the US. The project originally consisted of approximately 3600 ft of 72-inch-diameter microtunneling in the soft, glacial-age, varved clays of the Connecticut River Valley and about 1000 ft of open cut installation in miscellaneous fill soils. Key issues included microtunneling near the rock-soil interface and under active railroad tracks; mitigation of building, railroad, and adjacent utility settlement impacts and monitoring their performance; and construction in a crowded urban environment. Construction phase contractor proposed alternates implemented included about 600 ft of 15-inch-diameter pilot tube microtunneling, 600 ft of 72-inch-diameter microtunneling with an 1800 ft radius curve, and 200 ft of 72-inch-diameter pipe jacking all in lieu of portions of the original open cut areas.

- Granby 2/5 Microtunneling MDC CWP, Hartford, CT Performed design phase reviews, and a geotechnical baseline report (GBR) review. Also provided construction phase services including: review and recommendations related to launching and receiving shaft performance and settlement issues in soft varved silt and clay soils; and alignment tolerance and alignment control during microtunneling. Modifications to access shafts included jet grout stabilized entry and exit eye blocks.,
- Garden Street Microtunneling MDC CWP, Hartford, CT Performed design phase reviews, and a GBR review. Also provided construction phase services including review and recommendations related to: launching and receiving shaft performance and settlement issues in soft varved silt and clay soils; ground improvement at shaft eyes; and alignment tolerance and alignment control during microtunneling.
- Massport Telecommunications Cable, Boston, MA Prepared feasibility study regarding the applicability of and risks associated with trenchless construction methods for installation of a pair of fiber-optics cables along several alternative alignments under the and around the Reserve Channel in South Boston. Alternative alignments range from about 800 feet to 3500 long and horizontal directional drilling (HDD) (16-inch-diameter casing) and microtunneling (48-inch-diameter casing) methods of installation of casing pipe in soil and rock were evaluated. Key issues included presence of a high voltage cable crossing the alignments, future dredging of the waterfront area, miscellaneous fill materials and remnants of old waterfront structures, related structures and their foundations. Prime factors in the evaluation included technical feasibility, relative risk, site access, and cost.
- HDD Utility Installation, St. Mark's School, Southborough, MA Performed geotechnical studies and prepared HDD design recommendations for installation of a 4-inch-diameter HDPE casing for a sewerage force main passing under a pond and wetlands area. The HDD installation was 600 feet long and passed through glacial soils and bedrock. Geotechnical studies included borings, rock testing, and GPR survey of top of rock. Design included developing drill path and specification criteria. Also provided construction phase services.
- HDD Crossing, Rensselaer, NY Provided geotechnical and HDD design recommendations for installation of a
 3000-foot-long, 28-inch-diameter HDPE gray water pipe through soils under the Hudson River to bring water to a
 power facility. Tasks included reviewing geology and geotechnical as well as site access information to identify
 potential HDD alignments, preliminary evaluation of a drill path and pipe installation stresses, and HDD
 specifications.
- River Crossing, Plymouth, NH Developed design recommendations and specifications for replacement utility lines under the Pemigewasset River by horizontal directional drilling (HDD) methods. The HDD crossings are approximately 705 feet long each, and pass through glacio-fluvial and glacio-lacustrine deposits and a zone of soil reportedly contaminated with gasoline related products. The utilities include a 12-inch-diameter HDPE casing for a water line; a 12-inch-diameter HDPE casing for two telecommunications lines and a Fire Alarm line; a 6-inch-diameter HDPE for an electrical conduit; and an 10-inch-diameter HDPE casing for a sewer force main. Key issues included limited work areas, management of contaminated soils, impact of contaminated soils on the water line, and assessment of the risk associated with higher blow-count soils present along part of the alignment and evaluation of the potential for obstructions.

M. D. Boscardin
Biodata
Page 10
June 2013

• Cape Cod Canal Crossing, MA - Evaluation of geologic and geotechnical factors affecting the feasibility and risks associated with construction, using horizontal directional drilling, of an 18-inch-diameter natural gas pipeline under the Cape Cod Canal. Six crossing alignments ranging from 1,400 to 3,000 feet long were evaluated. Ground conditions included shallow bedrock, glacial till, end moraine, glacial outwash, and glacio-lacustrine and miscellaneous fill deposits. A key issue was the evaluation of the risk of encountering obstructions (cobbles and boulders) at each crossing alignment. The pipeline was constructed along one the crossing alignments identified and evaluated as having low risks relative to construction.

- Providence Harbor Crossing, RI Performed a post-construction review and evaluation of the design and
 construction of a 3,300-foot-long segment of an 18-inch-diameter natural gas pipeline crossing installed under the
 Providence Harbor using horizontal directional drilling methods that passed through fill, organic silt, glacial outwash
 and till, and shale and sandstone bedrock. Review and evaluation considered pre-construction information and
 decisions, contract specifications and conditions, compatibility of construction methods and equipment with ground
 conditions, construction control, and risk factors.
- East Boston Relief Sewer Rehabilitation, Boston, MA Performed subsurface investigations, prepared geotechnical and contaminated soil management design, a geotechnical baseline report (GBR), and construction recommendations and specifications for approximately 15,000 feet of sewer tunnel rehabilitation and replacement. Also provided construction phase services during initial lining and later microtunnel, in-line microtunnel and pipe-bursting construction. The project design included consideration of microtunneling, horizontal directional drilling, pipe bursting, pipe lining and cut-and-cover construction methods, ground modification in the form of jet grouting and permeation grouting, and related construction risks.
- Chestnut Street Drainage Project, Marblehead, MA Technical consultant/reviewer for an investigation
 to evaluate hard rock microtunneling options for an approximately 800-foot-long, 54-inch-diameter storm sewer
 outfall to be constructed through a bedrock knob adjacent to Marblehead Harbor. Provided a report summarizing our
 evaluation and construction recommendations, as well as, specifications for microtunneling and portal construction.
- Newtown Sewer Crossing, Newtown, CT Reviewed and developed recommendations for completion of construction of a sewer under an operating railroad by pipe jacking methods. Installation of the 42-inch-diameter steel casing had been stopped because blasting to remove rock at the jacking face had heaved the rail bed above. Tasks included reviewing the construction records for the railroad company to evaluate the potential causes of the heave; recommending measures to complete the construction while protecting the rail bed and maintaining rail traffic; and recommending measures to stabilize the rail bed in the heave zone and minimize the potential for a chronic maintenance problem at that location.
- Plateau Creek Pipeline, CO Performed geotechnical analyses and evaluations in connection with the preliminary geotechnical investigation and final design for replacement of the water pipeline. Evaluated alternatives for replacement of a 2,500-foot-long tunnel section that was in a deteriorated, unlined tunnel, in sandstone and shale. Also evaluated feasibility of using pipe jacking and microtunneling techniques to install several shorter, 48-inch-diameter pipeline segments in soil and rock at road and stream crossings. Final design activities included design, specification and, geotechnical baseline report review and revision for a 3,400-foot-long drill and blast tunnel (SEM/NATM) and a 10,000-foot-long, 20-foot-diameter TBM rock tunnel to house the 48-inch diameter water line. Served as technical reviewer of final design for tunnel and portal rock excavation and support.
- Lake Burnt Mills Dam, Suffolk, VA Provided geotechnical consultation and recommendations for replacement/rehabilitation of low level outlet buried pipelines, inlet/outlet structures, and valve and equipment buildings associated with a 45-ft-high, 1900-ft-long earth embankment dam impounding a 10,000-acre feet reservoir. Pipeline construction included underwater construction, conventional construction within cofferdams, and microtunneling through the dam while maintaining operation of the reservoir.

M. D. Boscardin
Biodata
Page 11
June 2013

• **Power Plant Diffuser System, Wiscasset, ME** - Performed geotechnical construction monitoring and testing associated with installation of a twin 9-foot diameter fiberglass cooling water pipeline on land and in the soft sediments of an estuary. Installed instrumentation to monitor pipe behavior during backfilling. Instrumentation included pneumatic total pressure cells and electrical resistance strain gages. Work included rock excavation, dike and embankment construction, subaqueous construction, and pipe bedding and backfilling.

- New Neponset Valley Sewer, MA Developed geotechnical design and construction recommendations and prepared specifications for small diameter (micro) slurry face tunneling and conventional pipe jacking for installation of a sewer force main under roads and railroad tracks and through an area of potentially contaminated soils. Considerations included evaluation of trenched and trenchless technologies, including ground freezing, jet grouting, permeation grouting and slurry walls, compatible with soil conditions and the environmental and space constraints of the site. Also performed review of contractor submittals, blast monitoring, and review of procedures and ground response data during tunneling under an active gas main during construction. Project included the construction of 8.4 miles of gravity and force main relief sewer up to 48 inches in diameter and construction of a pump station.
- Innerbelt, Road Rail Line Crossing, Somerville, MA Technical consultant for two pipe jacked crossings of MBTA and B&M rail lines to install a 48-inch-diameter steel casing pipe for ducts of electric and telecommunication lines. Supervised geotechnical investigation, preparation of contract documents, and application to rail lines for permission to install the crossing. This fast-track effort minimized engineering time to help minimize the impacts of long review time associated with rail line approval. Prepared a list of qualified contractors, assisted in evaluating bids, and observed construction of jacking pits and installation of the piping.
- Chelsea Creek Crossing, Chelsea, MA Technical Consultant for feasibility study of trenchless and direct burial crossings of the Chelsea Creek River to replace electric lines damaged by dredging of the river.
- Hultman Aqueduct Risk Analysis and Repair Design, Weston to Southboro, MA –. Technical reviewer and consultant during evaluation of the condition of the Aqueduct and related leaking. The Hultman Aqueduct is the principal water conduit for the Metropolitan Boston Area. Tasks included evaluation of the soil bedding supporting the Aqueduct to assess the risk to pipeline and leakage performance. The work included test pits excavated to expose the aqueduct near leak locations. Two test pits were extended to excavate beneath the active aqueduct.

Soil and Rock Slope, Dam, Dike Experience

- **Deerfield No.5 Hydroelectric Project, Monroe, MA -** Project Manager in for evaluation and design of remedial measures for hydroelectric plant canal dikes and conduit/tunnel along the Deerfield River. Issues included slope stability evaluation and upgrade, and seepage evaluation and control. Developed designs for dike improvements including slope and toe drainage, revised slope angles and heights, and a 250-foot-long, 12-foot diameter fiberglass pipe extension for the Conduit No. 2.
- San Vicente Dam Raise Project, San Diego County, CA Independent review of 90% Design Drawings, Specifications and Geotechnical Report for Package 2 Foundation Excavation, Access Roads, Dam Penetration, Tunnel and Piping, including soil and rock slopes and penetration of existing dam and dam foundation with a 9-ft-diameter tunnel for a low level outlet. The proposed dam raise is from about a 200-ft-high concrete dam to 300 ft high using roller compacted concrete (RCC).
- Rock Slope, Waltham, MA Performed stability analyses, and prepared design recommendations for slope stabilization and rockfall protection for 65-foot-high, 65° to 80° slope in diorite rock. The site had been occupied by an old wood structure and is being redeveloped with a new commercial structure that is near the toe of the slope.
- Cerrillos Dam, Puerto Rico Evaluated construction implications of rock excavation and support conditions for
 river diversion structures and dam foundation preparation. Evaluations included grouting to control seepage and
 excavation and support requirements for diversion tunnel and abutment excavations.

M. D. Boscardin
Biodata
Page 12
June 2013

• Rock Wall, Clifton, NJ - Performed stability analyses and provided design recommendations for an up to 120-foothigh rock slope with a slope angle of 70° and glacial till soil zones. Slope was part of an exhausted traprock quarry that is now being developed with buildings. The slope materials include glacial till and basalt overlying sandstone, siltstone and claystone. Key issues included investigation of and dealing very low strength seams in the claystone, controlling exposure and deterioration of the claystone using shotcrete and soil nails/rock dowels to prevent long-term undermining of the basalt above, and water control and drainage, including in near vertical fault related features. Project also included a 40-foot-high soil nail wall to support a glacial till slope above the rock.

- Rock Slope, Waltham, MA Performed stability analyses, rockfall analyses and prepared design recommendations rockfall protection and slope scaling and maintenance for 65-foot-high, 65° to 80° slope in diorite rock. The site had been occupied by an old wood structure and is being redeveloped with a new commercial structure that is near the toe of the slope. Later post construction worked with owner to evaluate risks associated with construction blasting on adjacent property relative to rock slope stability and performance.
- Larson Quarry, Dekalb, Illinois. Design recommendations for underground expansion of Larson Rock Quarry. Included design of open cut slopes and room and pillar mine in limestone and shale to be developed using drill and blast methods.
- Rocky Hill Quarry, Eliot, ME Project manager in charge of geotechnical investigations and design recommendations for a proposed 300-acre quarry. Scope of work included subsurface explorations, field reconnaissance, materials evaluations, investigation of rock slope stability conditions, hydrogeologic investigations and blasting program, and evaluation of impact of blast-induced vibrations on adjacent structures. Work included instrumentation and data monitoring for a seven-day pump test. Instrumentation included flow meters, pressure transducers, water level indicators, and automatic data acquisition systems.
- Llanarch Quarry, West Chester, Pennsylvania. Stability evaluation and recommendations for instrumentation and remediation of rock quarry walls. Included subsurface investigation and rock bolting recommendations.
- Metallic Mineral Mine Stability, Confidential Client Consulted on slope stability issues for several large open pit mines including underground conveyor tunnels processing chambers, some in excess of 200m deep. Examined stability parameter investigation and selection, controlling and managing ground water inflows, groundwater affects on stability, instrumentation and monitoring, and safety factors and reliability in analyses,
- Lake Ilo Dam Modifications. Dunn County, ND Task manager for the rock anchor testing program and development of rock anchor recommendations for concrete spillway stability improvements. The test program included testing four prototype anchors with 20- to 50-foot-long bond zones to evaluate capacity and creep characteristics for anchorages located in interbedded soft claystone and coal strata. Due to heterogeneity of the strata, anchors exhibited a "slip then stick" behavior during loading increase.
- Thornes Dam, Amenia, NY. Technical consultant and reviewer for the evaluation and design of repairs to this approximately 38-foot-high concrete gravity dam. The dam is considered a Class C "high hazard" dam. The project included subsurface explorations to determine foundation and seepage conditions, stability analyses, dam failure analyses to determine areas that would be inundated in the event of failure, and the evaluation of alternatives to increase the stability of the dam to acceptable levels. On the basis of the evaluation, rock anchors were designed to stabilize the dam.
- Lake Abeniki Dam, Dixville Notch, NH. Technical consultant and reviewer for the investigation and design of the reconstruction of this approximately 30-foot-high embankment dam. This Class C dam (high hazard) is located above a resort community and supplies water for fire protection, power generation, and manufacturing processes. The existing timber crib spillway had deteriorated and showed signs of bulging and instability. Also, uncontrolled seepage was observed along the toe of the embankment. GEI was engaged for the design of the reconstruction of the dam. The design includes new primary and auxiliary spillways, raising the dam by about 6 feet, and installation of toe drains to control seepage. A temporary cofferdam also was designed to stabilize the existing spillway pending reconstruction and to maintain the pond during removal of the existing spillway.

M. D. Boscardin
Biodata
Page 13
June 2013

• Arthur's Pond Dam and Upper Reservoir Dam, Cornwall-on-the-Hudson, NY. Technical reviewer the evaluation of Arthur's Pond Dam and Upper Reservoir Dam. Arthur's Pond Dam is a 27-foot-high earth embankment and masonry dam. Upper Reservoir Dam is a 33-foot-high earthen embankment dam. The initial evaluation involved the performance of stability analyses and the development of preliminary recommendations for the design of repairs to the dams. A preliminary evaluation of earthquake-induced liquefaction potential of the foundation soils beneath both dams was also conducted. Additional subsurface explorations and final design of the repairs are currently in progress.

- Harris Pond Dam, Nashua, NH. Project manager responsible for supervision of subsurface explorations,
 performance of stability and seepage analyses, and development of remedial design of repairs of a 35-foot-high
 masonry core wall embankment dam. Remedial repairs included construction of a new retaining wall,
 installation of permanent drains to control embankment seepage and to relieve hydrostatic pressures behind
 existing retaining walls, and strengthening existing retaining walls.
- **Cobble Mountain Dam, MA** Planned and performed cross-hole shear wave velocity tests to provide data for evaluation of seismic performance of a 263 ft high, 730 ft long; hydraulic fill dam completed 1932.
- Pogue Pond Dam, VT Project Manager in charge of subsurface investigations and engineering evaluation and recommendations to remediate seepage conditions in the slope of an embankment dam.
- Ambrosia Lake Facility, NM Evaluated Seepage and effectiveness of a partially penetrating slurry cutoff wall in
 a uranium tailings dam. The investigation included evaluation of the impact of the seepage and seepage control
 measures on the stability of the dam embankment.
- **Deer Lake Dam, Fishkill, NY** Project manager in charge of engineering evaluations to investigate and recommendations to remediate deteriorating seepage conditions in the slope of an embankment dam. Tasks included field explorations including piezometers, seepage analyses, and remedial design and monitoring recommendations.
- Route 106/Loudon Road Improvements, Concord, NH Project manager in charge of geotechnical construction
 observation services and geotechnical design recommendations for widening highways feeding into a regional mall.
 Construction included compaction control of embankment fills, subgrade and pavement structure compaction
 control, soil and rock slope improvements.
- Amherst, Massachusetts Evaluated design proposals for remediation of an unstable highway slope above a river.
- **Conway, Massachusetts** Investigated an unstable slope in till above a river and provided recommendations for protection of a structure located at the crest of the slope.

Foundation Experience

- South Windsor, CT Technical consultant for an industrial building expansion founded on silts and clays in the Connecticut River Valley. Key issues included bearing pressure evaluation and settlement estimates. Investigation and recommendations considered stress history of the soil profile based on geotechnical laboratory testing and prior construction/observations at the site. Given the amount filling needed to raise the grade at the site, monitored preloading of the site was included as a recommendation.
- **Foundations in Karst, Lopatcong, NJ** Provide review and consultation regarding design and construction of foundations for a large building with heavy column loads in an area where solution activity in the limestone bedrock had created karst conditions. The foundation system included a blend of large diameter drilled shafts and shallow spread footing.

M. D. Boscardin
Biodata
Page 14
June 2013

Tanker Offloading Facility, Fall River, MA - Provided feasibility/permitting phase consultation regarding the
geotechnical aspects of waterfront structures and dredging for a port facility. Evaluations include large (270-footdiamter) tank foundation alternatives, ground improvement, river bank and related dike slope stability, consideration
of trenched and trenchless options for installing pipeline to and offshore loading facility and dredged material
stabilization and on-site reuse. Performed site investigations including in situ testing to develop soil compressibility,
strength and liquefaction parameters.

- Central Artery, Tiedown Test Element Program, Boston, MA Task manager for designing rock and soil tiedown element test program, developing contract documents, evaluating bids for tiedown element installation and testing, monitoring instrumentation and field testing by the contractor, evaluation of test data, and preparation of a report describing the tests, the results and design recommendation. Instrumentation includes vibrating wire strain gages, electronic load cells, optical surveying, hydraulic pressure gages, and data acquisition.
- Peer Review, Pile Load Test Waiver, Boston, MA Two new elevators are being installed in the existing building and are to be supported by micropiles. Provided an independent evaluation in support of a request for a waiver of the requirement to perform a pile load test. The existing building is an 8-story brick structure, with a concrete slab foundation supported on caissons bearing in clay.
- I-95 Extension and I-395 Viaduct, Baltimore, MD Instrumented, performed and analyzed pile load tests to develop value engineering design recommendations for I-95 and I-395 interchanges. Instrumentation included electronic load cells, hydraulic pressure gages on rams, dial indicators, wire-mirror systems, telltales and optical surveying to monitor the load and movement of the test piles and reaction systems during compression and tension pile load testing. Pile types were H, pipe, Monotube, and mandrel-driven shell filled with concrete.
- Allied Hospital, Wilkes Barre, PA Geotechnical investigation and design for a four-story rehabilitation facility
 sited on strip mine spoil over four levels of abandoned coal mines. A test embankment was constructed and
 monitored to investigate potential deep-seated settlements and the potential for additional mine collapse and
 associated ground response were evaluated. Foundation was designed as structural mat to span potential subsidence.
- Baystate Medical Center, Phase 3, Spring Field, MA Provided geotechnical consultation and report, specification and drawing review to the project's geotechnical consultants for the Phase three addition with a footprint of approximately 85,000 sf immediately adjacent to existing hospital facilities include facilities with sensitive equipment such as MRI units, pathology laboratories and operating theaters. Key issues addressed include construction ground movements and vibration impacts associated with excavation and related temporary support walls for mat foundations on glacial till up to 40 feet below the ground surface and within 5 to 10 feet of existing facilities, instrumentation to monitor performance of the SOE and response of key facilities, slab under drainage and waterproofing. Assisted with alternatives review of methods to perform work within the strict noise, vibration and work area/access site constraints.
- Wharf Improvements, Portsmouth, NH Managed foundation design and construction recommendations for
 waterfront facilities improvements to accommodate larger vessels. Improvements include modification/replacement
 of the bowline mooring structure, construction of bow and breast line guide structures, replacement of the stern line
 mooring structure, construction of a cellular cofferdam dolphin, and dredging to enlarge and deepen the berthing
 area.
- **Eliot Hospital, Manchester, NH** Project Manager in charge of geotechnical investigations and foundation design for six- and eight-story additions to an existing hospital.
- Steeplegate Mall, Concord, NH Project Manager in charge of construction observations during site earth work, pavement construction, utility trench construction, wetlands outfall head wall, and site facilities installation for a 400,000-square-foot mall. Work also included geotechnical design recommendations to accommodate conditions encountered during construction.

M. D. Boscardin

Page 15

Biodata

June 2013

• Northeast Corridor Electrification Foundations, MA, CT, RI - Technical consultant for earth support system for installation of support foundations for electrification catenary support poles. Support systems installed within six feet of main passenger and freight rail lines in a variety of locations with varied sub-surface conditions.

- Underpinning, Building 150, Kittery, ME Project Manager in charge of contractor submittal review and construction observations during mini-pile installation to underpin a 3-story building at Portsmouth Naval Shipyard.
- Animal Care Facility, Amherst, MA Project Manager for subsurface investigations and foundation design recommendations for a three-story animal care facility for the University of Massachusetts. The new facility is adjacent to an existing building and impacts on the existing building were evaluated during design.
- Mill Valley Estates, Amherst, MA Geotechnical investigations, laboratory testing, and foundation design recommendations for a 35-acre development consisting of 3-story structures on a deep deposit of soft, varved clay.
- Agawam Alzheimer Facility, Agawam, MA Performed foundation investigations for a one-story wood frame
 facility with a footprint area of about 30,000 square feet on a 6 acre site. Investigations were preformed to provide
 data on the underlying varved clay, as well as, on the overlying sand and rubble fill materials. Foundation design
 and construction recommendations were developed for the building and associated parking areas, roadways, and cut
 and fill slopes.
- **Elementary School, Shutesbury, MA** Project manager in charge of subsurface investigations and foundation design recommendations for 100-foot by 200-foot elementary school addition.
- Temple Israel, Greenfield, MA Evaluated the condition of the super structure and the foundation of the building
 and developed recommendations for remedial measures to minimize future settlements, distortions and cracking.
- **Hadley, MA** Developed preliminary design recommendations for foundations for an equine center situated in an area of deep, Connecticut River Valley, varved clays.
- **Deerfield, MA** Developed preliminary design recommendations for foundations for a storage facility for Historic Deerfield. The site is underlain by terrace deposits of the Deerfield River.
- Amherst, MA Project manager in charge of field investigations, laboratory testing, and foundation recommendations for a nursing home facility at a varved clay site.
- Hope Creek Generating Station, Salem, NJ Evaluation of lateral and axial capacities of nuclear plant cooling tower foundation piles driven through marine clays.
- **Hadley, MA** Report regarding geotechnical investigation and foundation and pavement geotechnical design recommendations for a new automobile tire retail outlet.
- Village School, Royalston, MA Performed site investigations and prepared foundation design, slab-on-grade
 waterproofing and pavement subgrade recommendations for an approximately 14,000 sf new campus classroom
 facility for a private school. Foundations are to be constructed on glacial till using frost protected shallow
 foundation methods.
- Parking Garage, Storrs, CT Project Manager for subsurface investigations and foundation recommendations for a 4-story university parking garage in glacial till soils.
- Parking Garage, York, PA Designed H-Pile foundation alternative, including pile caps, for a 4-story parking facility.
- **DEC Educational Facility, Merrimack, NH** Project Manager in charge of subsurface investigations and foundation design recommendations for 65,000-square-foot auditorium building and 60,000-square-foot classroom building for Digital Equipment Corporation's Educational Facility.

M. D. Boscardin
Biodata
Page 16
June 2013

Contaminated Site Experience

• Soil Permeability Relative to No. 2 Fuel Oil, Leominster, MA – Developed testing program and performed computations to estimate site soil permeability relative to No. 2 Fuel Oil and amount of oil contained in the soil at the site of a fuel oil release.

- Abandoned Mine Evaluation, CA Part of team evaluation operational risks associated with acid mine drainage from an abandoned mine that produce iron, silver, gold, copper, zinc and pyrite from the 1860s to the 1960s. Evaluation included a brief inspection of the accessible portions of existing mine workings including viewing the condition of 5 to 10 year old repairs to mine supports as it pertains to continued operation of acid mine drainage abatement systems. In addition, soil and rock slope stability in the vicinity of mine portals and along pipelines conveying mine drainage and dams and impoundments on the site were evaluated relative to risks to operation of acid mine drainage abatement measures.
- Tidal Flats Vegetation Restoration, Everett, MA Managed restoration/enhancement of salt marsh vegetation in an intertidal area composed of historic fill. Tasks included field and laboratory testing to evaluate limiting factors for plant growth; greenhouse study to investigate compatibility of various plant rootstock with site soils; and planting and monitoring performance of 85,000 spartina alterniflora seedlings, 25,000 of a root-stressed variety and 60,000 of a saltwater nursery-raised seedling, in the tidal flats area.
- **Burlington, VT** Technical consultant for a feasibility study regarding MGP-contaminated sediment removal and capping options. Developed sampling and geotechnical testing program to provide base parameters for evaluating feasibility of various dredging and capping options.
- MGP SOE, Haverstraw, NY Consultation regarding support of excavation and dewatering design for excavation
 to remove MGP contamination. Reviewed alternatives for excavation within 5 feet of adjacent structures, related
 instrumentation to monitor excavation and building performance. Issues included ground movement and vibration
 effects on buildings and utilities and working beneath a temporary enclosed to control odors and off-gassing during
 excavation.
- Dredged Material Management Plan, Massachusetts Coastal Zone Management Managed preliminary geotechnical investigations and a sediment decontamination technology assessment for the Dredged Material Management Plan (DMMP) in support of major navigational dredging operations at four ports in the Commonwealth of Massachusetts. Preliminary geotechnical investigations included the review, analysis, and compilation of existing geotechnical data on the harbors of Fall River, Gloucester, New Bedford, and Salem. Sediment decontamination technology screening was conducted to evaluate alternative remedial technologies that potentially apply to the treatment of sediments that are not suitable for conventional aquatic or upland disposal due to elevated contaminant concentrations. As part of this technology assessment, we conducted a survey of over 100 vendors of treatment technologies. Based on the results of this survey, we developed a sediment treatment technology database containing current information for each technology in several major comparative categories including: ability to treat various contaminant types, effects of sediment characteristics on the treatment process, potential role of the vendor in a sediment decontamination project, capabilities and logistical requirements of the process equipment, and information on current and projected costs.
- MTA Maintenance Facility, Chicopee, MA Project manager for investigation and evaluation of releases
 associated with fuel USTs and development of remedial action measures. Work at the site included passive soil gas
 screening, drilling and monitoring well installation, soil and ground water sampling and analysis, and coordination
 with facility personnel to maintain traffic flows during field work.

M. D. Boscardin
Biodata
Page 17
June 2013

Former MGP Site, Spencer, MA - Technical specialist to support MCP Phase III and Phase IV activities at the site.
 Remedial actions at the site included grading the site, removing excess materials from the site, and construction a pavement on the site to serve as a barrier restricting access and infiltration to underlying soils containing coal tar related contaminates including PAHs. The paved area was designed to serve as a municipal parking facility.
 Contaminated soils removed from the site were screened and sent to a licensed utility boiler for disposal/recycling.

- MCP Immediate Response Action (IRA), Former Manufactured Gas Plant (MGP) Site, Salem, MA Managed feasibility study (FS) and design of an IRA to address a condition of Substantial Release Migration (releases of sheens, low pH groundwater, and DNAPL) to a surface water body. The IRA included a FS to identify and screen potential response alternatives to address site conditions. The selected alternative designed includes a horizontal drain for a DNAPL recovery system and a funnel and gate system to treat groundwater leaving the site. Funnel options considered included slurry walls, drive HDPE sheet piles, and trenched insertion of a rolled HDPE sheet. The trenched insertion of the rolled HDPE sheet toed into a clay-confining layer at a depth of approximately 23 feet was selected for design. The treatment includes a limestone gate/permeable wall to raise groundwater pH followed by a powdered activated carbon (PAC)/sand gate to address dissolved VOCs. In another portion of the site, a DNAPL recovery system consisting of recovery wells has been designed. Air sparging to create a biofence to address dissolved VOCs is planned downgradient of the recovery wells.
- Former MGP Site, Providence, RI Managed monthly and annual post closure monitoring. Tasks at the site
 included monthly monitoring of groundwater wells for the presence of immiscible phase product and annual
 monitoring of groundwater quality per state requirements. Also investigated groundwater conditions as related to
 pipeline corrosion and monitored subsurface conditions revealed during aboveground fuel oil storage tanks at site.
- Former MGP Site, Salem, NJ Provided technical support for the proposed excavation of contaminated soils adjacent to a tidal creek in Salem, New Jersey. The project includes excavation to various depths below the water table, relocation of a railroad line to allow excavation within the right-of-way, and treatment of contaminated groundwater from dewatering. Engineering analyses include excavation support design, and groundwater modeling to estimate dewatering quantities and resulting treatment costs. The predicted dewatering quantities were used in cost comparisons of construction alternatives. Considered various options for water control including slurry walls and jet grout base slabs.
- Former MGP Site, Egg Harbor, NJ Performed excavation support system design peer review. Excavation support system was part of a former MGP site remediation program that included excavation of contaminated soils which were then treated thermally. After treatment, soils were re-used to refill the excavation. The excavation support system included cantilevered and tied-back steel sheet piling. Issues considered included water control, depth of excavation, base stability, wall stability, wall movement, constructability of the system as designed, and risks associated with the proposed system.
- Stormwater Culvert Rehabilitation, Everett, MA Project Manager for inspection and evaluation of the condition of a 1600-foot-long, 5.5-foot-wide by 10-foot-high pipe arch culvert, and for analysis, design, and construction of repairs including a 100-foot-long, long-span, aluminum drainage culvert replacement section in contaminated soils performed as a URAM and miscellaneous spot repairs in other sections of the culvert. The work included research of corrosion and constructability issues, presenting design options to client, design of repairs and preparation of construction specifications, evaluation and routing of storm water flows, investigation of soil and sediment contamination and selection of disposal options for 3000 tons of contaminated soil surrounding the damaged culvert section and 160 tons of sediment from within the culvert, and providing construction oversight and management services
- Warehouse Redevelopment, Hatfield, MA Technical specialist during remedial activities during redevelopment
 of a warehouse facility. Former facility at site used inks and pigments, and contamination associated with MEK and
 MIBK was encountered during redevelopment construction activities and removed from the site. Investigated the
 extent and feasibility of removal of contaminated soils under building foundations, performed indoor air quality
 monitoring, and worked on expediting contamination removal activities while complying with regulations during the
 transition from old to new MCP.

M. D. Boscardin
Biodata
Page 18
June 2013

Cutoff Walls Experience

• Herbert Hoover Dike Rehabilitation Project, Reach 1, Seepage Cut-Off Wall Martin and Palm Beach Counties, FL – Reviewed and evaluated, for the Contractor, construction records, field permeability tests, laboratory permeability and strength tests, core logs, core photographs, and televiewer logs from a 500-foot-long, 80-foot-deep (50 feet in soil and 30 feet in limestone, 2-foot-thick continuous slurry wall installed using a hydromill and self-hardening cement-bentonite slurry for conformance with project performance criteria. Key issues included in-place permeability, wall continuity and features observed in the borehole/televiewer photographs. Developed supplemental and modified procedures to verify wall conformance. Our evaluation supported the Contractor's successful construction of the wall. The 500-foot demonstration wall was a precursor to construction of a 3-milelong segment of slurry wall by the same methods.

- Feather River Levee Slurry Wall, Marysville, CA Technical consultant for design and construction cement bentonite and soil bentonite slurry walls to improve levee stability during flood events. Approximately, 13,000 feet of slurry wall construction, up to 65 feet deep is planned, with the first phase of about 5000 feet currently under construction. Reviewed plans and specifications, assisted with submittal reviews and participated in start up slurry wall construction and training of field inspection staff.
- Containment Slurry Wall, Canadys, SC Technical consultant for forensic investigating of an existing soil-bentonite slurry containment wall in the dikes surrounding a coal ash pond. The ash pond was approximately 95 acres with about 8,300 feet of slurry wall. Later, developed and supervised laboratory mix design, compatibility testing, and permeability testing programs for a Portland cement, slag cement and bentonite slurry containment wall, then performed calculations and prepared drawings and specifications for containment wall design and construction including slurry wall mix performance, instrumentation and testing protocols, jet grout closure details at locations of penetrations through the slurry wall/dike.
- Containment Slurry Wall, Confidential Client, MA Provided technical support during the design and construction observation for a soil-bentonite slurry wall constructed to contain low pH brine. The wall was approximately 1 meter thick, 510 long and 5 to 11 meters deep. A key issue was the compatibility of the slurry wall components with the brine. Design included compatibility testing of the proposed material with brine from the site and long-term hydraulic conductivity testing of the proposed and as-build slurry mix.
- Spectacle Island, Boston Harbor, MA Provided technical assistance during the preparation of design and construction recommendations for a soil-bentonite slurry wall constructed to control landfill leachate migration. The wall is approximately 3 feet thick, 1,300 feet long, and up to 35 feet deep. Design issues investigated include mix design to achieve the desired hydraulic conductivity and compatibility of soil, bentonite, and leachate.

Miscellaneous

- Steam Chambers, Kern County, CA Laboratory testing and geotechnical design for oil sand stream extraction caverns. The extraction system included horizontal drilling to install pipes for injection of steam and extraction of oils.
- Underground Storage Caverns, Fort Saskatchewan, Canada Finite element analyses and design recommendations for deep caverns in salt rock formation for storage of natural gas. Caverns were approximately 250 feet in diameter and 6,000 feet deep. Included consideration of creep behavior.
- Coal Mine Subsidence, Illinois Evaluated causes and impacts and developed recommendations for remedial
 measures in regions of coal mine subsidence for the Abandoned Mined Lands Reclamation Council. Remedial
 measures included backfilling and grouting to fill mined voids and to arrest ground movements. Project work
 included borehole photography, design, installation, and monitoring of instrumentations to provide data on
 settlement and horizontal movement of the ground and affected structures.

M. D. Boscardin
Biodata
Page 19
June 2013

• Granite Curbing Investigation, NH, MA, and NC - Principal investigator in charge of evaluating the properties and performance characteristics of granite curbing from various sources. Testing included density, compressive and tensile strength, durability, and freeze-thaw resistance.

- Ballast Test Section, Broken Bow, NE Principal investigator in charge of installation of test section and monitoring performance of five types of rock ballast on a mainline for Burlington-Northern Railroad and Meridian Aggregates.
- Concrete Tie Center Binding Investigation, Bill, WY Project manager for field investigation and evaluation of railroad track bed soil conditions affecting life and performance of concrete ties.
- Shoulder Ballast Cleaning Study, Bushnell, IL Project manager for field investigation to study effectiveness of shoulder ballast cleaning on ballast life and track bed performance.
- Crash Wall Evaluation, AAR Test Facility, Pueblo, CO Performed geotechnical and structural analyses of a retaining structure that serves as a crash wall to test railroad vehicles. The existing wall was to be subjected to a higher test crash load, 3,000,000 pounds, than in the past during and up coming tank car test. Analyses included soil berm resistance, sliding resistance of the structure, overturning/rocking resistance of the structure, as well as, ability of the concrete and steel components of the structure to resist the higher loading. Recommendations included placement of accelerometer instrumentation to document the response and movement of the crash wall structure during the test.
- Prebid, Value Engineering, and Other Evaluations Performed analyses and developed construction and value engineering alternatives for contractors during the bidding phases of projects involving tunnel and open-cut excavations in soil and rock. Included evaluation of compatibility of proposed construction methods and equipment with the expected ground conditions, effect of excavation-induced ground movements on adjacent structures and utilities, and recommendation of measures to minimize potential adverse response. Techniques evaluated include, slurry walls, sheet pile walls, soldier pile and king pile walls, soil nail walls, MSE walls, deep dynamic compaction, deep soil mixing, jet grouting, permeation grouting, compaction grouting, compensation grouting, secant pile walls, in situ densification by vibration, stone columns, wick drains and other geotechnical construction methods. Included projects in Canada, Puerto Rico, Washington, D.C., Milwaukee, Chicago, Phoenix, Washington and Florida.

PUBLICATIONS

K.A. Pidgeon, M. Boscardin, W.S. Riehl, Burlington Tunnel Emergency Repairs: A Case History, <u>Proceedings</u>, <u>2011 Rapid Excavation and Tunneling Conference</u>, SME, June 2011, pp. 1438-1446.

M.C. Ensign, D. Pottle, M. Radville, and M. D. Boscardin, **Managing Existing Contamination Impacts on Design and Construction of an Urban Microtunneling Project**, <u>Proceedings No-Dig 2010</u>, North American Society for Trenchless Technology, Chicago, IL, May 2010.

P. A. Roy, M. D. Boscardin and A. J. Miller, **Pittsburgh North Shore Connector Tunneling Project – Overview and Update**, Hong Kong Tunnelling Conference, The Institution of Materials, Minerals, and Mining, Hong Kong Branch, November 2009.

- A. Miller, P. Roy, and M. Boscardin, **Making the North Shore Connection,** Tunnels and Tunneling North America, Vol. 33, Conway, NH, May 2009, pp. 13-15.
- K. A. Wargo, P. A. Roy, M. D. Boscardin, A. J. Miller, and K. DiRocco, **Tight Fit Tunneling**, <u>Civil Engineering</u>, Vol. 79, Issue No. 3, ASCE, Reston, VA, March 2009, pp. 58-65.
- P. A. Roy, M. D. Boscardin and A. J. Miller, **Allegheny River Tunnel Crossing Project**, <u>Proceedings of North American Tunneling 2008</u>, Editors: M. Roach, M. Kritzer, D. Ofiara, and B. Townsend, SME, June 2008, pp. 587-593.
- A. J. Miller, M. D. Boscardin and P. A. Roy, North Shore Connector Tunnel Project, Pittsburgh, USA, Proceedings The 13th Australian Tunnelling Conference, Melbourne, Australia, Australian Institute of Mining and Metallurgy, Pub. Series No. 3/2008, Carleton Victoria, Australia, May 2008, pp 247-252.
- M. D. Boscardin, **What Will Happen Next Door?**, Geo-Strata. Volume 9, Issue 1, ASCE, Reston, VA, January/February 2008, pp. 20-25.
- M. D. Boscardin, P. A. Roy, A. J. Miller and K. J. DiRocco, **Designing to Protect Adjacent Structures during Tunneling in an Urban Environment**, <u>Proceedings</u>, 2007 Rapid Excavation and Tunneling Conference, Ed. M.T. Traylor and J.W. Townsend, SME, June 2007.
- M.D. Boscardin, C. Patterson, M. Landis, J-C. Younan, and D. Aghjayan, **Evaluation of Permeability of Containment Slurry Walls**, Proc. GeoCongress 2006, ASCE, Atlanta, February 2006.
- M. D. Boscardin, P.A. Roy, L.A. Becker, K.J. DiRocco, and K.E. Wood, **Movements Due to Freezing, Thawing and Tunneling Beneath Two Buildings**, <u>Proceedings</u>, <u>2005 Rapid Excavation and Tunneling Conference</u>, Ed. J.D. Hutton and W. D. Rogstad, SME, June 2005.
- H.S. Lacy, M.D. Boscardin, and L. A. Becker, **Performance of Russia Wharf Buildings During Tunneling**, <u>Proceedings of North American Tunneling 2004</u>, Editor: L. Ozdemir, AUA, Atlanta, GA, April 2004, Balkema, pp. 121 128.
- S. L. Pearlman, M. P. Walker, and M. D. Boscardin, **Deep Underground Basements for Major Urban Building Construction**, <u>Proceedings GeoSupport 2004 Drilled Shafts</u>, <u>Micropiling</u>, <u>Deep Mixing</u>, <u>Remedial Methods</u>, and <u>Specialty Foundations</u>, <u>GSP No. 124</u>, Ed. J. P. Turner and P. W. Mayne, ASCE, Orlando, FL, January 2004, pp. 545 560.
- T. W. Kahl, L.J. Welch, Jr., M.D. Boscardin, S. Morrow, **Design and Construction of a Slurry Wall to Contain a Low- pH Dense Aqueous Phase Brine**, Proceedings Soil Rock America, Boston 2003.
- M. D. Boscardin, **Building Response to Construction Activities**, Proceedings of Earth Retention Systems 2003: A Joint Conference, Presented by ASCE Metropolitan Section Geotechnical Group, The Deep Foundations Institute, and ADSC: The International Association of Foundation Drilling May 6 and 7, 2003, New York City pp. 171-185.
- M.D. Boscardin and M.P. Walker, **Design of Large Thrust Pits for Tunnel Jacking on Boston's Central Artery Project**, World Tunnelling, November, 2000.
- M.D. Boscardin, M.P. Walker, W.P. Konicki, and H. van den Elsen, **Design of Large Thrust Pit for Jacked Box Tunnels.** Proceedings of the North American Tunneling 2000, Underground Construction: "The Revolution Continues," Boston, Massachusetts, June 6-11, 2000, pp. 333-341.

M. D. Boscardin

Page 21

Biodata

June 2013

L.W. Abramson and M.D. Boscardin, **Tunnel Rehabilitation**. <u>Proceedings of the Third National Conference on Geo-Engineering for Underground Facilities</u>, Editors: G. Fernandez and R. A. Bauer Sponsored by the Geo-Institute of the ASCE, University of Illinois at Urbana-Champaign, June 1999, pp. 912 - 924.

- M.D. Boscardin, and M.P. Walker, **Ground Movement, Building Response, and Protective Measures**, <u>Effects of Construction on Structures</u>, <u>GSP No. 84</u>, Proceedings of sessions of GeoCongress 98, sponsored by the Geo-Institute of the ASCE, Boston, Massachusetts, October 1998.
- N.A. Campagna, M.D. Boscardin, and G.R. Iglesia, **Tension Element Testing in South Bay and Downtown Boston for CA/T Project**, <u>Special Geotechnical Testing</u>: <u>Central Artery/Tunnel Project in Boston</u>, <u>Massachusetts</u>, <u>GSP No. 91</u>, Editor: J.R. Lambrechtes, Proceedings of sessions of GeoCongress 98, sponsored by the Geo-Institute of the ASCE, Boston, Massachusetts, October 1998.
- M.D. Boscardin, Editor, **Jacked Tunnel Design and Construction**, **GSP No. 87**, Proceedings of a session on tunnel jacking at GeoCongress 98, sponsored by the Geo-Institute of the ASCE, Boston, Massachusetts, October 1998, pp. 63.
- M.D. Boscardin, M.P. Walker, M.Y. Mahoney, M.L. Jones, and J.M. Callanan, **Design and Construction of a Barrier Wall and Reaction Window Treatment System for MGP**, <u>Proceedings of the 10th Annual IGT Symposium on Gas, Oil, and Environmental Biotechnology and Site Remediation Technologies</u>, Orlando, Florida, December, 1997.
- M.D. Boscardin, R.L. Wooten and J.M. Taylor, **Pressure Balance Shield Pipe Jacking to Avoid Contamination**, <u>Trenchless Pipeline Projects</u>, <u>Practical Applications</u>, Editor: L. Osborn, ASCE, Boston, Massachusetts, June 1997, pp.135-142.
- M.D. Boscardin, R.L. Wooten, and J. M. Taylor, **Pipe Jacking to Avoid Contaminated Groundwater Conditions**, Proceedings, 13th Rapid Excavation and Tunneling Conference, SME, June 1997.
- M.D. Boscardin, M.T. Mahoney, M.L. Jones, M.P. Walker, and J.M. Callanan, **Reaction Wall Treatment of Ground Water at a Former MGP Site**, <u>Proceedings of the 11th Annual Conference on Contaminated Soils</u>, Editors: Calabrese and Kostecki, Lewis Publishers, Chelsea, Michigan, October 1996.
- M.D. Boscardin, G.R. Iglesia, and M.L F. Bode, **Full-Scale Tiedown Tests for the Central Artery/Tunnel Project**, Civil Engineering Practice, Jour. of Boston Soc. of Civil Engrs. Section, Spring/Summer, 1996, pp. 51-78.
- B.I. Collingwood, M.D. Boscardin, and R.F. Murdock, **Abating Coal Tar Seepage in Surface Water Bodies Using Sheet Piles with Sealed Interlocks**, <u>Symposium on Dredging and Containment of Contaminated Sediments</u>, ASTM STP 1293, K.R. Demars, G.N. Richardson, R.N. Yong, and R.C. Chaney, Eds., American Society for Testing and Materials, Philadelphia, 1995, pp. 220-226.
- M.D. Boscardin and D.W. Ostendorf, **Barrier Walls to Contain Contaminated Soils**, <u>Principles and Practices for Petroleum Contaminated Soils</u>, Editors: Calabrese and Kostecki, Lewis Publishers, Chelsea, Michigan, 1993, Ch. 19, pp. 433-449.
- M.D. Boscardin and I. Ahmed, **Subsidence Effects on Buildings and Buried Pipelines**, <u>Proceedings: Third Workshop on Surface Subsidence Due to Underground Mining</u>, Editor: S.S. Peng, Dept. of Mining Energy, West Virginia University, Morgantown, pp. 106-112, June 1992.
- M.D. Boscardin, E.T. Selig, R.S. Lin and G. W. Yang, **Hyperbolic Parameters for Compacted Soils**, <u>Journal Geotechnical Engineering</u>, ASCE, Vol. 116, No. 1, pp. 88-104, January 1990.
- M.D. Boscardin and D. W. Ostendorf, **Cutoff Walls to Contain Petroleum Contaminated Soils**, <u>Petroleum Contaminated Soils</u>, <u>Vol. 2</u>, Editors: Calabrese and Kostecki, Lewis Publishers, Michigan, Ch. 20, pp. 233-250, 1989.

M. D. Boscardin

Page 22

Biodata

June 2013

E.J. Cording, G.S. Brierley, J.W. Mahar and M.D. Boscardin, **Controlling Ground Movements During Tunneling**, The Art and Science of Geotechnical Engineering at the Dawn of the Twenty-First Century, <u>A Volume Honoring Ralph B. Peck</u>, Editors: Cording et al., Prentice Hall, Englewood, N.J. 1989, Ch. 25, pp. 477-505.

- M.D. Boscardin and E.J. Cording, **Building Response to Excavation-Induced Settlement**, <u>J. Geotech. Engrg.</u>, <u>ASCE</u>, Vol. 115, No. 1, January 1989, pp. 1-21.
- M.D. Boscardin, **Impact of Tunneling on Two Brick-Bearing-Wall Structures**, Proceedings Second International Conference on Case Histories in Geotechnical Engineering, 1988.
- M.D. Boscardin, **Building Response to Excavation-Induced Ground Movements**, Ph.D. Dissertation, University of Illinois, Urbana, Illinois, 1980.
- M.D. Boscardin, E.J. Cording and T.D. O'Rourke, **Case Studies of Building Behavior in Response to Adjacent Excavation**, Final Report, UMTA-IL-06-0043-78-1 prepared by the University of Illinois at Urbana-Champaign for the U.S. Dept. of Transportation, Washington, DC, 1978.
- M.D. Boscardin and T.D. O'Rourke, **Building Response to Ground Movements Caused by an 18-m-Deep Excavation**, Proceedings of the Conference on Large Ground Movements and Structures, UWIST, Cardiff, Wales, 1977.
- E.J. Cording, T.D. O'Rourke and M.D. Boscardin, **Ground Movements and Damage to Structures**, International Conference on Evaluation and Prediction of Subsidence, Pensacola Beach, pp. 516-537, January 1978.
- T.D. O'Rourke, E.J. Cording and M.D. Boscardin, **Damage to Brick Bearing Wall Structures Caused by Adjacent Braced Cuts and Tunnels**, Proceedings of the Conference on Large Ground Movements and Structures, UWIST, Cardiff, Wales, 1977.
- T.D. O'Rourke, E.J. Cording and M.D. Boscardin, **The Ground Movements Related to Braced Excavation and Their Influence on Adjacent Buildings**, Report UIUC-ENG-76-2023 for the US Dept. of Transportation, Office of the Secretary and Federal Railroad Administration, Washington, DC, DOT-TST-76T-23, August 1976.

\\server\data\marco\BCE\MDBResumes\MDB ResumeJanuary2013.doc